



## CeBeCo® **ROWAMAT® „DT“**

### Pipe washing system in continuous pulsing procedure

- For linkage with sawing centres and end piece processing systems and available as single system
- With operating capacities of up to 1,200 units/hour, depending on linkage and pipe dimensions
- With minimum installation effort

## CeBeCo<sup>®</sup> ROWAMAT<sup>®</sup> „DT“

### Construction

The CeBeCo<sup>®</sup> ROWAMAT<sup>®</sup> „DT“ (double drum) is made of thick, welded high-grade sheet steel. Designs or sizes according to customer-specific request are possible. Aqueous cleaners are used.

### Equipment

Direct electrical heater, insulation, digital thermostat, high-pressure submersible pump, coarse filter insert, drying facility, vapour extraction, double drum with direct drive.

### Supplementary features

Oil separator for non-emulsified oils in bypass mode, micro-filter in the main stream (surface filter), micro-filter in the bypass (depth filter), soil protection basin, loading stations (in various designs), drainage pump, weekly clock.

### Types

TYPE DESIGNATION	RL 60 DT
PIPE LENGTHS (MM)	600
PIPE DIAMETER (MM)	von 8 - 34 oder 10 - 60

The illustrations on this page show also special equipment that are not included in the standard scope of delivery. The contents comply with the status at the date of publication (03/16). We reserve the right to implement changes to construction and equipment. Screen colours only reproduce an approximation of the actual colour hue. Surcharge for the displayed special equipment.

Quality and Experience since 1932