



## CeBeCo<sup>®</sup> **SECURUS - D**

### Spray-wash system for small parts

- Made of thick welded high-grade sheet steel
- Available in two standard sizes as well as individual intermediate and special sizes
- For use with aqueous cleaners

## CeBeCo<sup>®</sup> SECURUS - D

### Function/Fields of use

The components to be washed are in a slewing ring and pass by the nozzle fittings attached at the top, side and bottom; they are showered with heated cleaning agents by spraying method. This spraying method ensures the cleaning success for a broad range of parts.

### Equipment

Direct electrical heater, insulation, digital thermostat, submersible pump, stainless steel nozzle system, coarse filter insert, rotating plate with direct drive.

### Supplementary features

Increase of operating weight, oil separator for non-emulsified oils in bypass mode, micro-filter in the main stream (surface filter), micro-filter in the bypass (depth filter), vapour extraction, drying facility, air micro-filter, soil protection basin, fill level monitor, drainage pump, weekly clock.

### Types

TYPE DESIGNATION	Size 2	Size 3
SLEWING RING - Ø (MM)	600	1.000
WORKING HEIGHT (MM)	400	500
OPERATING WEIGHT (KG)	100	200
CLEANING AGING QUANTITY (L)	200	350
HEATER (KW)	6	12
INSULATION (MM)	25	25

The illustrations on this page show also special equipment that are not included in the standard scope of delivery. The contents comply with the status at the date of publication (03/16). We reserve the right to implement changes to construction and equipment. Screen colours only reproduce an approximation of the actual colour hue. Surcharge for the displayed special equipment.

Quality and Experience since 1932