



CeBeCo® **TROWAMAT® „KOMBI“**

Spray/flood cleaning system

- Spraying process - for bulk materials
- Flooding method - for components to be washed with problem areas
- Flexible drive system - optionally with four movement variations

CeBeCo® TROWAMAT® „KOMBI“

Construction

The CeBeCo® TROWAMAT® „KOMBI“ is made of strong welded high-grade sheet steel and is manufactured as standard according to the two-tank principle, but further tanks can be integrated upon request. Intermediate or special sizes according to customer-specific request are possible. Aqueous cleaners are used.

Equipment

Rinsing facility, direct electrical heater, insulation, digital thermostat, high-pressure submersible pumps, stainless steel nozzle system, coarse filter insert, drying facility, vapour extraction, running wheel with direct drive, pneumatic door lock.

Supplementary features

Ultrasonic equipment, oil separator for non-emulsified oils in bypass mode, micro-filter in the main stream (surface filter), micro-filter in the bypass (depth filter), interval blow-off system, recirculating air drying, air micro-filter, soil protection basin, loading station (in various designs), drainage pump, weekly clock.

Types

TYPE DESIGNATION	6040/28	12540/28	18540/28	12080/90
CAGE DIMENSIONS (LxWxH in MM)	600 x 400 x 280	1250 x 400 x 280	1850 x 400 x 280	1200 x 800 x 900

Model variants



The illustrations on this page show also special equipment that are not included in the standard scope of delivery. The contents comply with the status at the date of publication (03/16). We reserve the right to implement changes to construction and equipment. Screen colours only reproduce an approximation of the actual colour hue. Surcharge for the displayed special equipment.

Quality and Experience since 1932