



CeBeCo[®] **TROWAMAT**[®]

Spray-wash system with running wheel

- Running wheel control: automatic turning for bulk goods; automatic swivelling for sensitive components to be washed
- The strong pump capacity enables less use of chemicals and fast washing times
- Compact construction

CeBeCo® TROWAMAT®

Construction

The CeBeCo® TROWAMAT® is made of thick welded high-grade sheet steel and is available in four standard sizes. Intermediate or special sizes according to customer-specific request are possible. Aqueous cleaners are used.

Equipment

Direct electrical heater, insulation, digital thermostat, high-pressure centrifugal pump, stainless steel nozzle system, coarse filter insert, oil separator for non-emulsified oils in bypass mode, drying facility, vapour extraction, running wheel with direct drive, pneumatic door, single loading roller track.

Supplementary features

Rinsing facility, increase of operating weight, micro-filter in the main stream (surface filter), micro-filter in the bypass (depth filter), interval blow-off system, recirculating air drying, air micro-filter, soil protection basin, loading station (in various designs), drainage pump, weekly clock.

Types

TYPE DESIGNATION	6040/28	8045/40	10060/60	12080/90
CAGE DIMENSIONS (LxWxH in MM)	600 x 400 x 280	800 x 450 x 400	1000 x 600 x 600	1200 x 800 x 900

Model Variants



The illustrations on this page show also special equipment that are not included in the standard scope of delivery. The contents comply with the status at the date of publication (03/16). We reserve the right to implement changes to construction and equipment. Screen colours only reproduce an approximation of the actual colour hue. Surcharge for the displayed special equipment.

Quality and Experience since 1932